

Direct Color Systems®

SMALL-FORMAT UV LED FLATBED PRINTERS

VERSATILE MAX-VOLUME, SMALL-FORMAT SOLUTIONS WITH INDUSTRY-LEADING PRINT QUALITY, SPEEDS AND CAPABILITIES

ALL NEW FEATURING 304MM / 12" PRINT WIDTH

ENHANCED THROUGHPUT OVER PREVIOUS MODELS*



UNMATCHED CAPABILITIES

- >> TEXTUR3D™ 3-dimensional prints for a unique look and feel, plus standard flat prints
- >> Produces ADA-compliant/Braille signage (Patented)
- >> Cylindrical object and bottle printing made easy with the EasyCyl attachment
- >> Printable area: up to 304mm x 610mm (12" x 24")
- >> Models vary with fully adjustable heights to accommodate substrates from 0mm to 102mm (4"), 152mm (6") and 381mm (15")
- >> Print on wood, metals, ceramic tiles, plastics, glass, industrial parts, promotional products and so much more!
- >> F6 Editions capable of printing directly to light & dark colored t-shirts and garments (Patent Pending)

OPTIMIZE YOUR PRODUCTION

- >> Inline printing – print any combination of white, color and clear print head channels simultaneously, inline, in a single pass
- >> Bulk Ink System™ – Unlike single-use cartridges, this system allows for 100% utilization of available ink
- >> White Ink Circulation System – Programmable and automatic circulation of the entire white ink tank and lines
- >> ACS™ – UV print head anti-cure system
- >> LED sensors automatically adjust head height to reduce print head strikes
- >> Made in the USA – distributed globally

INCLUDED RIP 10 SOFTWARE INTEGRATES SEAMLESSLY WITH INDUSTRY-STANDARD DESIGN PROGRAMS (PHOTOSHOP®, ILLUSTRATOR®, COLOR BYTE, CORELDRAW®)

*INCREASED THROUGHPUTS ARE FILE AND RESOLUTION DEPENDENT. DETERMINE OPTIMAL RESOLUTION PRIOR TO DETERMINING THROUGHPUT.


SUPREME PRINT QUALITY

- >> Y-axis absolute positioning accuracy and repeatability of ±.038mm (0.0015") when utilizing the Y-axis Heavy-Duty Direct Drive Module
- >> Precision Dot Control™ provides industry-leading print quality
- >> White UV ink creates a very opaque image, allowing you to print vibrant colors onto virtually any colored or transparent substrate
- >> UV LED inks offer outstanding solvent and abrasion durability – 6-color ink set, including clear and white

LCD TOUCH SCREEN PROVIDES INTERACTIVE, ON-DEMAND PRINTER STATUS AND INK LEVELS

Direct Color Systems®
1800z

ALL NEW



SMALL-FORMAT UV LED FLATBED PRINTERS

ALL MODELS ARE AVAILABLE IN STANDARD IR2 OR F6 EDITIONS*
ECONOMICAL HEAD REPLACEMENT COST | ADJUSTABLE POWER OUTPUT FOR UV LED LAMP

DIRECT JET 1800z SERIES UV LED PRINTER SPECIFICATIONS

IMAGING PROCESS	On-demand inkjet (Micro Piezo) 8-channel head with 180 nozzles/inch/channel
RESOLUTION	Text & Graphics: 720X720 Production: 720X1440, 1080X1440 / Quality: 1440X1440, 2880X1440, 5760X1440
INK DROPLET SIZE (MINIMUM / MAXIMUM)	1.5 picoliters / 21 picoliters
INK COLORS	Yellow, Magenta, Cyan, Black, 2x White, 2x Clear
INK DELIVERY SYSTEM	Bulk Ink System™ User refillable 300mL Tanks (1800z15c - 15mL Fillable Cartridges)
PRINT SPEED³	110 to produce a bi-directional 8" x 10" (203mm x 254mm) image at 1440 x 720 dpi / High Speed 306 to produce a bi-directional 10" x 24" (254mm x 610 mm) image at 1440 x 720 dpi / High Speed
Y-AXIS ABSOLUTE POSITIONING ACCURACY & REPEATABILITY⁴	±0.038mm // ±0.0015"
PRINT DIRECTION	Uni- and bi-directional
MAXIMUM PRINTABLE AREA⁵	304.8mm x 609.6mm // 12" x 24" for all standard print modes.
MAXIMUM SUBSTRATE SIZE	330.2mm x 660.4mm // 13" x 26"
Z-AXIS (DEPTH/THICKNESS CONTROL)	1800z10: 0cm to 10cm (4") // 1800z15: 0cm to 15cm (6") // 1800z35: 0cm to 38cm (15")
MEDIA	Prints to a variety of substrates ⁶ using DCS Multisolve LED UV IR2 or IRF6 ink set, including (but not limited to) plastic, glass, wood, ceramic, metal, etc. IRF6 ink prints to t-shirts, belts, bags and more. ⁷
CONTROL PANEL	89mm (3.5") Color LCD Touch Screen Display
INTERFACE	Hi-speed USB 2.0
WINDOWS OPERATING SYSTEM	Windows 7 (32 & 64 bit), Windows 8 (32 & 64 bit) or Windows 10 (32 & 64 bit)
SYSTEM MINIMUM REQUIREMENTS	CPU of >3GHz, 8GB RAM, 100 GB free hard disk space and 4 available USB 2.0 ports
POWER SOURCE	100-240 VAC, 50-60 Hz., 4 A auto switching
OPERATING STANDING AND STANDBY TEMPERATURE	16°C - 26°C (60°F - 80°F)
HUMIDITY	Non-condensing 20%-80%
OPTIONAL ACCESSORIES	EasyCyl, Vacuum Table, ADA/Braille Module, DTG, Automated URL Design
WEIGHT	1800z35: 230 lbs. (104 kg) / 1800z15: 220 lbs. (100 kg) / 1800z10: 220 lbs. (100 kg)
DIMENSIONS	1800z10, 1800z15, 1800z35: Depth 31.8" (806.7mm) x Height 25.5" (647mm) x Width 48.8" (1239.4mm). Height of 40.8" (1036mm) when cover is fully opened. 1800z35: Depth 31.8" (806.7mm) x Height 33.9" (861mm) x Width 48.8" (1239.4mm). Front cover is removal for service accessibility.
AGENCY LISTINGS	CE pending
WARRANTY	Printer 1-year limited warranty
RIP	Color Byte RIP 10
INK AND MEDIA	Available through Direct Color Systems and authorized dealers / distributors

*F4 Editions available as custom order.

¹ Substrate dependent. ² Substrate dependent. ³ Print times may vary dependent on computer configuration. ⁴ When utilizing the Y-axis Heavy-Duty Direct Drive Module. ⁵ Non-standard print modes are limited to 298mm (11.75") in print width. ⁶ All substrates should be tested for image receptivity, adhesion and durability, with final acceptance and suitability determined by the customer. ⁷ Some materials may require the use of an adhesion promoter or a chemical wipe prior to printing to promote adhesion. ⁸ To prevent contamination of the ink system, operators of the machine must only use the compatible ink specified for each machine. Failure to do so will harm the machine and void the warranty.

This data sheet is for informational purposes only. Direct Color Systems makes no warranties, expressed or implied in this summary. Specifications are subject to change without notice. This is not an offer for sale.

DCS CORPORATE 99 HAMMER MILL ROAD, ROCKY HILL, CT USA 06067
800-693-6376 | +1 860-829-2244 | INFO@DIRECTCOLORSYSTEMS.COM

DCS EAA RUA DO ALTO DAS TORRES 942. 4430-009 VILA NOVA DE GAIA, PORTUGAL
EAAINFO@DIRECTCOLORSYSTEMS.COM

F⁶ EDITION NOW AVAILABLE

With IRF6 inks, cracking and peeling of prints is eliminated or minimized on flexible items. ⁸

